

PD 3.0 20W

6N-201WU00

WALL-MOUNT
(Fixed type)

Features:

- Universal AC Input 90~264Vac
- Regulated Output With Low Ripple Noise
- 100% burn in test
- 1 year warranty
- CEC,DoE Level VI,ErP
- WEEE / ROHS 2.0 / REACH 2.0
- Safety : UL/cUL.PSE.CB
- Case Size : 32.5*30.0*31.0mm

Model No.	O/P Voltage	O/P Current	O/P Watts
6N-201WU00	5.0V	3.0A	15.0W
	9.0V	2.2A	19.8W
	12.0V	1.67A	20.04W



Specification:

Input	Voltage	AC 90V~264V Universal Full Range
	Frequency	47-63Hz
	Current	500mA
	Leakage Current	< 0.25mA
Others Protection	Start up time	< 3000mS @115VAC Full Load
	Rise time	<20mS
	Hold up time	>20mS @ 230Vac/50Hz input
	Protection	OCP/OVP/SCP
	Cooling	Natural Convection Cooling
Environment	Temperature	Operating: 0~40°C;Storage: -10~+70°C
	Humidity	Operating: 20%~85%;Storage: 10%~95%(Non Condensing)
M.T.B.F	30K Hours MIL-HDBK-217F @115VAC/ 230VAC Full Load Ambient : 25°C	
Safety Regulation	UL 62368-1, CSA C22.2 No.62368-1, IEC62368-1, EN62368-1	
	UL 60950-1, CSA C22.2 No.60950-1, IEC60950-1, EN60950-1	
EMC	EMI	FCC CFR 47 PART 15B
Energy Efficiency	Average active efficiency	> 81.38% Min @ 230Vac / 50Hz input
	No-load power consumption	> 0.1W Min @ 230Vac / 50Hz input

製品に関するお問合せや見積り依頼は

トキトレーディング株式会社

☎079-560-7333

✉ info@tokitrading.co.jp

〒669-1342 兵庫県三田市四ツ辻710
www.tokitrading.co.jp

